

SBS[®]X-75A

Sealed Connector



Dust - Water - Shock

SBS[®]X-75A



Male Plug

The SBS[®]X-75A sealed waterproof connectors come in multiple configurations offering up to a maximum of 140A of power and the durability of up to 5,000 mating cycles. Positive metal latches help safeguard against accidental disconnects that may be caused by vibration, while the built-in cable clamp allows for strain relief on wires.



Female Receptacle

The compact sleek high-power design of these environmentally rugged connectors makes them ideal for outdoor applications. The IP68 weatherproof rating ensures that the connector will be free of water for full protection up to 30 minutes at 6 feet in the mated conditions, or with the use of covers in unmated condition.



Panel Mount Receptacle

FEATURES

- Power & Signals or Ground
- Rated for IP68 Ingress Protection
- Positive Latching to Secure Connection for Vibration Applications
- Operating Temperatures -20°C to 105°C
- 5,000 Mating Cycles

TARGET MARKETS

- Industrial/Commercial
- Power Equipment
- Material Handling/Automation
- Agricultural/Construction
- Lawn/Garden Equipment
- Marine



Panel Mount Plug



Does your next project need Ingress Protection against harsh environments?

Contact your Representative today to learn more about this new connector series.

ANDERSON POWER[™]

Your Best Connection[™]

Anderson Power Products[®]
13 Pratts Junction Road
Sterling, MA 01564-2305 USA
T: +1 978-422-3800
www.andersonpower.com

pactech

Data Center Cable Solutions &
Smart Industrial Connectivity
Est. 1994, San Jose, California

Pactech



2260 Trade Zone Blvd.
San Jose, CA 95131 USA
T: +1 408-526-9363
sales@pactech-inc.com
www.pactech-inc.com

SBS[®]X-75A



Dust - Water - Shock

Power & Signals IP68 Cable Assemblies

	LLL	P/N
 <p>AP-SBSX-75A-MF1-LLL</p> <p><u>Power</u>: 6 AWG UL1015 <u>Data</u>: 4x 20 AWG</p>	025	AP-SBSX-75A-MF1-025
	050	AP-SBSX-75A-MF1-050
	075	AP-SBSX-75A-MF1-075
	100	AP-SBSX-75A-MF1-100
	200	AP-SBSX-75A-MF1-200
	300	AP-SBSX-75A-MF1-300
 <p>AP-SBSX-75A-MF2-LLL</p> <p><u>Power</u>: 12 AWG UL1015 <u>Data</u>: 4x 18 AWG</p>	025	AP-SBSX-75A-MF2-025
	050	AP-SBSX-75A-MF2-050
	075	AP-SBSX-75A-MF2-075
	100	AP-SBSX-75A-MF2-100
	200	AP-SBSX-75A-MF2-200
	300	AP-SBSX-75A-MF2-300

All high voltage wiring harness products are in compliance with:

[Product Design Analysis] [Terminal Crimping Mold Design] [Terminal Crimping Mold Processing] [Terminal Crimping] [Data Traceability System]